(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 18 March 2004 (18.03.2004)

(10) International Publication Number WO 2004/023227 A2

(51) International Patent Classification7: 19/44

G05B 19/04,

(74) Agent: BRIDGE-BUTLER, Alan, James; G.F. Redfern & Co., 7 Staple Inn, Holborn, London WCIV 7QF (GB).

(21) International Application Number:

PCT/GB2003/003872

(22) International Filing Date:

3 September 2003 (03.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0220564.9

4 September 2002 (04.09.2002)

(71) Applicant (for all designated States except US): FORAC LIMITED [GB/GB]: Brunswick Street East, Hove, East Sussex BN3 1AU (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BUNYARD, Adam [GB/GB]; 7 Tongdean Rise, Brighton, East Sussex BN1 5JG (GB).

(81) Designated State (national): US.

(84) Designated States (regional): European patent (AT. BE. BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU. IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK.
- of inventorship (Rule 4.17(iv)) for US only

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ACTUATOR CONTROL DEVICE

(57) Abstract: A valve actuator control device adapted to control the position of a valve actuator by means of solenoid valves. in which if the actuator position deviates from a desired position, but remains within a predetermined distance from said desired position, the control device is adapted to only return the actuator to the desired position after a delay period, thereby to increase the life span of said solenoid valves.